



tesa® Powerstrips Self-Adhesive Hooks S, Oval

Product Information

BNR 57533, 58275, 57519, 57543

Product Description

Small self-adhesive plastic bathroom and kitchen hook. Removable fixation to safely hang up anything weighing up to 1 kg. Oval design available in white, chrome, matt-chrome and modern matt black color

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without trace thanks to the Powerstrips technology
- Made from high quality plastic
- Usable on tiles, glass, wood, plastic and a variety of other surfaces*
- Hooks reusable with tesa Powerstrips SMALL
- Completely covered tesa Powerstrip

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

- How to apply - Step by step:1. Clean the surface with alcohol or silicone-free glass cleaner
2. Apply the Powerstrip® Small strip on the surface - press for 5 seconds minimum
3. Open the hook and stick the back of the hook onto the strip - press for 5 seconds minimum
4. Close and snap-lock the hook.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|------|
| • Type of adhesive | synthetic rubber | • Hook shape | Oval |
| • Holding power up to | 1 Kg | • Silicone free | yes |



tesa® Powerstrips Self-Adhesive Hooks S, Oval

Product Information

Properties/Performance Values

• Application temperature from	+15 °C	• Residue-free removability	yes
• Application temperature to	+35 °C	• Reusable	yes
• Applicationfield	Bathroom, Kitchen	• Reusable with	Powerstrips Small
• Area of use	Indoor	• Solvent free	yes
• Batteries included	no	• Suitable surfaces	Glazed Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics, Metal
• Batteries required	no	• Temperature resistance	yes
• Chemical Resistance	no	• Temperature resistance max.	35 °C
• Hazard material	no	• Temperature resistance min.	15 °C
• Humidity sealing	no	• UV resistant	no
• Material	PS (polystyrene)	• Water resistance	no
• Oil and grease resistance	no	• Waterproof	no
• Ozone resistance	no		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>