



tesa® Powerstrips Waterproof Hook, Plastic



Product Information

BNR 59701

Product Description

The self-adhesive tesa Powerstrips Waterproof Hooks Plastic are versatile bathroom and kitchen hooks for damage-free fixation without the need to drill holes.

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 2 kg
- Removable without a trace due to the Powerstrips® Waterproof technology
- Made from high quality plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower*
- Especially developed for wet areas (e.g. shower, bathtub etc.)
- Hooks reusable with tesa Powerstrips Waterproof

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

Application Fields

- How to apply - step-by-step:
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation - wait for 10 seconds minimum
 3. Apply the Powerstrip Waterproof Large strip on the surface - press for 5 seconds minimum
 4. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
 5. Let the hook slide down on the base plate until it is locked

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 2 Kg | • Silicone free | yes |



tesa® Powerstrips Waterproof Hook, Plastic

Product Information

Properties/Performance Values

• Application temperature from	-15 °C	• Residue-free removability	yes
• Application temperature to	35 °C	• Reusable	yes
• Applicationfield	Bathroom, Kitchen	• Reusable with	Powerstrips
• Area of use	Indoor		Waterproof Large
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Chemical Resistance	no		
• Hazard material	yes	• Temperature resistance	yes
• Humidity sealing	yes	• Temperature resistance max.	35 °C
• Material	PS (polystyrene)	• Temperature resistance min.	15 °C
• Oil and grease resistance	no	• UV resistant	no
• Ozone resistance	no	• Water resistance	yes
		• Waterproof	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>