



# tesa® Professional Mirror Mounting

## Product Information



BNR 55734, 55758, 55733, 55759, 55732, 55760, 65204

## Product Description

tesa® Powerbond MIRROR is a quick and convenient way to permanently hang mirrors and other flat objects in humid areas.

## Product Features

- Ideal for mirrors
- Humidity-resistant
- Holds mirrors of max. 70 x 70 cm up to 4 mm thickness
- Suitable for humid areas like bathrooms

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |         |                   |         |
|--------------------|---------|-------------------|---------|
| • Backing          | PE foam | • Total thickness | 1150 µm |
| • Type of adhesive | acrylic |                   |         |

## Properties/Performance Values

- |                                |   |                               |   |
|--------------------------------|---|-------------------------------|---|
| • Ageing resistance (UV)       | yes   | • Humidity resistance         | yes                                       |
| • Application temperature from | -10 °C  | • Residue-free removability   | no  |
| • Applicationfield             | Bedroom, Children's room, Hall, Home, Living room, Office, Bathroom | • Reusable                    | no  |
| • Area of use                  | Indoor  | • Suitable surfaces           | Tiles, Most plastics, Glass, Metal, Steel |
| • Batteries included           | no  | • Temperature resistance max. | 40 °C                                     |
| • Batteries required           | no  | • Temperature resistance min. | 10 °C                                     |
| • Chemical Resistance          | no  | • UV resistant                | yes                                       |
| • Hazard material              | no  | • Waterproof                  | no  |



# tesa<sup>®</sup> Professional Mirror Mounting

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>