



tesa[®] 66740

Product Information

400µm d/s differential foam tape with removable adhesive

Product Description

tesa[®] 66740 is a black double-sided foam tape with a PET reinforcement. The tape is equipped with a special ultra-removable adhesive on one side and a tackified acrylic adhesive on the other side.

Product Features

- Excellent removability on various substrates
- Excellent resistance stability to demanding environmental conditions
- Waterproof: IPX7

Application Fields

- Automotive electronics display mounting
- Removable mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing | PE foam | • Total thickness | 400 µm |
| • Type of adhesive | tackified acrylic | • Color | black |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|--------------------------|------|
| • Elongation at break | 94 % | • Ageing resistance (UV) | good |
| • Tensile strength | 32.2 N/cm | • Humidity resistance | good |

Adhesion to Values

- | | | | |
|-------------------------|----------|---------------------------------------|-----------|
| • Steel (initial) | 0.5 N/cm | • Steel (covered side, after 14 days) | 11.5 N/cm |
| • Steel (after 14 days) | 0.6 N/cm | • Steel (covered side, initial) | 8 N/cm |



tesa[®] 66740

Product Information

Additional Information

Liner: PV50 transparent PET-film (50µm; 72g/m²)

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=66740>