



tesa® 51324

Product Information



High Crepe Paper Belting Tape

Product Description

tesa® 51324 is a high crepe paper belting tape with a strong natural rubber adhesive. tesa® 51324 is used for various applications, especially for belting of yarn beams, coil bandages and splicing of photo papers or veneers. The very high conformability of the backing provided by the high crepe paper structure and the strong natural rubber adhesive makes the tape very suitable for adhering to rough surfaces or complicated shapes and contours.

<span style="background-color: var(--palette-white, #ffffff); color: var(--attrpanel-color-text, #1a2028)

Product Features

- Very high conformability for excellent bonding to rough and irregular surfaces
- Strong natural rubber
- adhesive for good bandoliering performance

Application Fields

- tesa® 51324 is used for various applications, especially for belting of yarn beams, coil bandages and splicing of photo papers or veneers
- The high crepe paper belting tape is ideally suited for adhering to rough surfaces or complicated shapes and contours

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 280 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|---------|
| • Elongation at break | 17 % | • Tensile strength | 47 N/cm |
|-----------------------|------|--------------------|---------|

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=51324>



tesa[®] 51324

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51324>