



# tesa<sup>®</sup> 50658 PV42



## Product Information

Double-sided splicing tape

## Product Description

tesa<sup>®</sup> 50658 PV42 is a 120 µm translucent double-sided splicing tape consisting of a non-woven carrier coated with an acrylic adhesive, covered by a brown paper liner.

## Product Features

- The special adhesive formulation ensures a secure bond on a variety of paper materials, even at elevated temperatures
- With its high adhesive coating weight, tesa<sup>®</sup> 50658 PV42 offers an especially high tack for a safe initial bond even on rough and heavy paper grades

## Application Fields

- Splicing of paper (liner and flute) in corrugated board production
- Splicing of paper in newsprint and converting processes
- Splicing of heavy paper and cardboard

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |           |                   |        |
|--------------------|-----------|-------------------|--------|
| • Backing          | non-woven | • Total thickness | 120 µm |
| • Type of adhesive | acrylic   | • Color of liner  | brown  |
| • Type of liner    | glassine  |                   |        |

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50658>