



tesa® 4386

Product Information



Aluminum Tape with electrically conductive adhesive

Product Description

tesa® 4386 is a pressure sensitive adhesive tape based on a 40 micron aluminum foil, an electrically conductive acrylic adhesive and a white siliconized paper liner (65 µm).

Product Features

- Conductive backing
- Conductive adhesive

Application Fields

- electrostatic and EMI/RFI shielding
- Cable wrapping

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|----------------------|----------|
| • Backing | aluminium foil | • Color of liner | white |
| • Type of adhesive | conductive acrylic | • Thickness of liner | 65 µm |
| • Type of liner | paper | • Thickness of tape | _NULL µm |
| • Color | silver | | |

Properties/Performance Values

- | | | | |
|----------------------------------|------------|---|-------------------|
| • Elongation at break | 6 % | • Liner release force | 2 N/cm |
| • Tensile strength | 30 N/cm | • Operation temperature up to | 180 °C |
| • Backing appearance (visual) | reflective | • Surface resistance x-y-direction (adhesive) | 0.25 Ohm / square |
| • Contact resistance z-direction | 5 mOhm | • Surface resistance x-y-direction (backing) | 0.2 Ohm / square |

Adhesion to Values

- | | | | |
|-----------|----------|---------|--------|
| • Backing | 3.5 N/cm | • Steel | 3 N/cm |
|-----------|----------|---------|--------|



tesa[®] 4386

Product Information

Additional Information

Test method for contact resistance using a 1 kg electrode and a 1 square inch contact surface

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04386>