



tesa[®] 6930 silver matt/ black text



Product Information

Laser-Markable Film, tamper-proof and self-adhesive

Product Description

tesa[®] 6930 is a two-layer laser markable film with a high-performance adhesive. The brittle product construction ensures that the label is destroyed upon any attempt of removing and tampering and leaves a visible trace (damage of information and label).

Marking and cutting are achieved by laser in one step, which makes it possible to realize any desirable label variation and format using only one material.

Product Features

- Marked irreversible by laser with excellent long-term legibility
- Reliably withstand stresses over the long-term covering a wide range of applications
- Manipulation leaves visible trace (damage on information and label)
- Not removeable without destruction of the label to prevent re-using
- Just-in-time production replaces a multitude of pre-made labels and reduces storage needs
- Available in different colors

Application Fields

Used as a tamper evident identification label over the entire lifetime of a product and also as a data carrier system for intelligent in-process steering

Laser marking ensures high flexibility and quick adaptation of format and contents, e.g. languages, sequential serial numbers

High contrast and marking precision support the realization of even the smallest letters, numbers and symbols, even 2D-bar codes (data matrix, QR codes) and ensures clear information appearance and easy and correct legibility by the human eye or scanning devices.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|---------------------|---------------------|
| • Backing | Acrylic | • Adhesive weight | 25 g/m ² |
| • Type of adhesive | acrylic | • Thickness of tape | 110 µm |
| • Type of liner | coated paper | | |

For latest information on this product please visit <http://l.tesa.com/?ip=06930>



tesa[®] 6930

silver matt/ black text

Product Information

Product Assortment

- Available colors black matt, black, silver, white

Properties/Performance Values

- | | | | |
|--------------------------|-----------|-------------------------------------|----------------------------------|
| • Ageing resistance (UV) | very good | • Suitable laser | CO ₂ , Nd:YAG, Yb:YAG |
| • Chemical Resistance | very good | • Tamper evidence | yes |
| • Frost resistance | -40 °C | • Temperature resistance long term | 120 °C |
| • Humidity resistance | very good | • Temperature resistance short term | 250 °C |
| • Shelf life time | 12 months | | |

Adhesion to Values

- Steel 1.8 N/cm

Storage Conditions

Storage Conditions

23°C, 50% RH, stored in original box

Original packaging excluding exposure of tapes to light and heating source

Storage of rolls in a horizontal position

Ideal storage at standard room temperature and rel. humidity according to ISO 554

Refrigerated tapes need to be reconditioned prior to their use. An application below 10°C must be avoided as this may not provide sufficient immediate bonding

After opening the packaging, the tape shall be used as soon as possible

Additional Information

Standard Dimensions:

Width: 100mm and 120mm. Length: 300m

Assortment and Technical Data:

6930 PV3 black glossy / white text: Adhesive 25g/m², Thickness 95µm without Liner. Color code: 04

For latest information on this product please visit <http://l.tesa.com/?ip=06930>



tesa[®] 6930

silver matt/ black text

Product Information

Additional Information

6930 PV3 black matt/ white text: Adhesive 25g/m², Thickness 95µm without Liner. Color code: 28

6930 PV3 silver glossy/ black text: Adhesive 25g/m², Thickness 110µm without Liner. Color code: 35

6930 PV3 silver matt/ black text: Adhesive 25g/m², Thickness 110µm without Liner. Color code: 34

6930 PV8 white glossy/ black text : Adhesive 25g/m², Thickness 120µm without Liner. Color code: 08

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06930>