

# tesa® CaRes 51913 PV11

**Product Information** 

Repulpable double-sided splicing tape

# **Product Description**

tesa<sup>®</sup> CaRes 51913 is a thin double-sided repulpable tape consisting of a tissue paper and a modified water soluble acrylic adhesive.

# **Product Features**

- Very high shear strength
- Very high heat resistance
- Very good adhesion values on most paper grades
- tesa 
  © CaRes 51913 is certified by independent laboratories for: Repulpability according to TAPPI UM-213 over full pHrange (pH3 – pH9)
- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO3)
- Paper from well-managed certified forests and other controlled sources

# **Application Fields**

tesa® CaRes 51913 is particularly suitable for

- Permanent overlapped splices
- Core starting
- Manual as well as automatic application

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

# **Product Construction**

•	Backing	non-woven	•	Total thickness	65 µm			
•	Type of adhesive	repulpable tackified	•	Color	blue			
		acrylic						
•	Type of liner	repulpable siliconised						
		paper						
Properties/Performance Values								

# **Properties/Performance Values**

•	Static shear resistance	very good	• Tack	
---	-------------------------	-----------	--------	--

# **Additional Information**

Other products for permanent overlapped splicing:

• tesa® 51912 - better bonding on heavier paper grades

For latest information on this product please visit http://l.tesa.com/?ip=51913



medium



# tesa® CaRes 51913 PV11

**Product Information** 

# Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 09/11/24 – en-US