



tesa® EasySplice 51948 FilmLine Black X



Product Information

tesa® 51948 EasySplice FilmLine Black X

Product Description

tesa® 51948 EasySplice FilmLine Black X is an integrated flying splice tape consisting of a black PET backing and very high tack contact adhesive

Product Features

- tesa® 51948 EasySplice FilmLine Black X is particularly suitable for Flying splices in the flexography or rotogravure printing industry of flexible packaging material with high content of slip agents

Application Fields

Main product feature

- Very high tack contact adhesive
- Black PET backing
- Excellent wetting properties

Customer benefits:

- Secure splicing performance on high slip films at high speeds
- Fast and easy splice preparation
- Easy waste detection

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|------------------|----------------------|
| • Backing | PET | • Color | black |
| • Type of adhesive | synthetic rubber | • Color of liner | white with tesa logo |
| • Total thickness | 115 µm | | |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|---------------------------|-----------|
| • Tensile strength | 70 N/cm | • Static shear resistance | medium |
| • Shelf life time (packed) < 25°C | 18 months | • Tack | very good |



tesa® EasySplice 51948 FilmLine Black X

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51948>