



tesa[®] LUUP double towel bar, self-adhesive, chromed metal

Product Information

BNR 40294

Product Description

The self-adhesive tesa[®] Luup double towel bar can be easily applied to a wall. No drilling is required, keeping walls as they are. The holder is beautiful, glossy and rounded – a fine addition to your bathroom. It can be taken down effortlessly and without a trace. Reuse is simple, requiring a new adapter BK20-2.

Product Features

- Double towel bar, with tesa[®] Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Simple to take down without a trace and remount elsewhere with new adapter BK20-2
- Easy application without drilling
- Product dimensions: 50mm x 600mm x 120mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------------|-----------------------|-------|
| • Type of adhesive | Silane modified polymer | • Holding power up to | 12 Kg |
|--------------------|-------------------------|-----------------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|---------------------|---|
| • Applicationfield | Bathroom | • Reusable | yes |
| • Chemical Resistance | no | • Reusable with | Adapter BK20-2 |
| • Curing time | 12 hour(s) | • Solvent free | yes |
| • Material | Chromed metal | • Suitable surfaces | Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood, Most plastics |
| • Residue-free removability | yes | • UV resistant | yes |



tesa[®] LUUP double towel bar, self-adhesive, chromed metal

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>