

# tesafilm® Eco & Crystal Mini Dispenser

# **Product Information**



BNR 59038, 59039

## **Product Description**

tesafilm® Eco & Crystal offers a strong adhesive performance whilst being completely transparent. High-quality adhesive tape from tesa® with a pioneering manufacturing process. Accompanied by a mini tape dispenser made from 100% recycled plastic (housing).

### **Sustainable Aspects**

tesafilm® eco & crystal: 90% post consumer recycled PET (PCR PET) in film backing core: 100% recycled plastic (PIR)

#### **Product Features**

- Product with sustainable contribution: The backing material is made of 90% recycled PET bottles
- · High-quality, transparent tape: A clear and reliable adhesive tape that's invisible on most surfaces
- · Top performance adhesive: The tape is tear resistant and maintains its stickiness over time
- Silent unwinding: The tape comes off its roll without making a sound \*Easy to use: Compatible with all tesafilm® tape dispensers tesafilm Mini dispenser included
- 90% Recycled content: UL2809 certified (ECVP Environmental Claim Validation Procedure)
- Recyclability tested using the INGEDE-Method 12: Does not affect cardboard reprocessing

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Max. core diameter

•	Backing	PET film	•	Total thickness	44 µm
•	Type of adhesive	water-based acrylic			

#### **Properties/Performance Values**

•	Elongation at break Tensile strength Adhesive strength Ageing resistance (UV) Hand tearability Low noise unwinding Material	100 % 43 N/cm High adhesion yes no yes	•	Reusable Roll width max Serrated blade Solvent free Suitable surfaces Tear resistance	yes 19 mm yes yes Paper, Cardboard yes
	Max roll length	Recycled PS (polystyrene) 10 m		Transparency Unwind force	good 3 N/cm



# tesafilm® Eco & Crystal Mini Dispenser

**Product Information** 

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

