



# tesa<sup>®</sup> Roller Permanent Glue ecoLogo<sup>®</sup>, Disposable



## Product Information

BNR 64347, 59090, 59171

## Product Description

When it comes to precision and lasting results, the tesa<sup>®</sup> Roller Permanent Gluing ecoLogo<sup>®</sup> disposable is the convenient way to apply glue for reliable adhesion.

## Product Features

- Made from 100% recycled plastic (housing)
- Strong adhesion
- Clean, fast & permanent bonding
- Glues paper, cardboard, photos
- Reddish glue shows where adhesive has been applied
- Tear resistant backing (PET)
- Solvent free
- Tape length: 8.5m
- Tape width: 8.4m

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Type of adhesive                      acrylic

## Properties/Performance Values

- |                             |                              |   |  |
|-----------------------------|------------------------------|---|--|
| • Material                  | Recycled PS<br>(polystyrene) | • Solvent free                              | yes                                      |
| • Residue-free removability | no                           | • Suitable for right and/or left<br>handers | For right and left<br>hander             |
| • Reusable                  | no                           | • Suitable surfaces                         | Paper, Cardboard,<br>Most plastic, Glass |



# tesa<sup>®</sup> Roller Permanent Glue ecoLogo<sup>®</sup>, Disposable

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>