



tesa[®] LUUP Wall Hook, Self-Adhesive, Chromed Metal



Product Information

BNR 40291

Product Description

It's simple to attach the self-adhesive tesa[®] Luup bath wall hook to a wall without drilling. Surfaces remain unscathed. The hook's round glossy design makes it a beautiful accessory. It can be removed without a trace whenever you like. Moving it to another location is also simple, requiring only a new adapter BK73.

Product Features

- Bath wall hook, with tesa[®] Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Easily removable without a trace and can be moved elsewhere with new adapter BK73
- Convenient attachment without drilling
- Product dimensions: 33mm x 33mm x 30mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 5 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------|------------------------|-----------------------------|--------------|
| • Applicationfield | Bathroom | • Residue-free removability | yes |
| • Chemical Resistance | no | • Reusable | yes |
| • Design series | tesa [®] LUUP | • Reusable with | Adapter BK73 |
| • Humidity resistance | yes | • Shape of wall piece | Round |
| • Material | Chromed metal | • Solvent free | yes |
| • Number of hooks | Single, Double | • UV resistant | yes |



tesa[®] LUUP Wall Hook, Self-Adhesive, Chromed Metal

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>