

# tesa® Powerstrips Self-Adhesive Hook L

**Product Information** 

BNR 58055, 58045

## **Product Description**

tesa Powerstrips Hooks Large Trend are bathroom and kitchen hooks with a trendy look. Plus they are removable and reusable hooks for maximum flexibility.

#### **Product Features**

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 2kg
- Removable without trace thanks to the Powerstrips® technology
- · Made from high quality plastic
- Usable on tiles, glass, wood, plastic and a variety of other surfaces\*
- · Hooks reusable with tesa Powerstrips LARGE
- · Completely covered tesa Powerstrip

### **Application Fields**

How to apply - Step by step: 1. Clean the surface with alcohol or silicone-free glass cleaner

- 2. Apply the Powerstrip Large strip on the surface press for 5 seconds minimum
- 3. Disengage the base plate of the hook and stick it onto the strip press for 5 seconds minimum
- 4. Let the hook slide down on the base plate until it is locked

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
•	Holding power up to	2 Kg	•	Silicone free	yes

<sup>\*</sup>Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



## tesa® Powerstrips Self-Adhesive Hook L

## **Product Information**

## **Properties/Performance Values**

<ul> <li>Application temperature from</li> <li>Application temperature to</li> <li>Applicationfield</li> <li>Area of use</li> <li>Batteries included</li> <li>Batteries required</li> <li>Chemical Resistance</li> <li>Hazard material</li> <li>Humidity resistance</li> </ul>	+15 °C +35 °C Bathroom, Kitchen Indoor no no no no	<ul> <li>Ozone resistance</li> <li>Residue-free removability</li> <li>Reusable</li> <li>Reusable with</li> <li>Solvent free</li> <li>Suitable surfaces</li> </ul>	no yes yes Powerstrips Large yes Glazed Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics, Metal
<ul><li>Humidity sealing</li><li>Material</li></ul>	no PS (polystyrene)	<ul><li>Temperature resistance</li><li>Temperature resistance max.</li></ul>	yes 35 ℃
Oil and grease resistance	no	Temperature resistance min.	15 °C
		<ul> <li>UV resistant</li> </ul>	no
		<ul> <li>Water resistance</li> </ul>	no
		<ul> <li>Waterproof</li> </ul>	no

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

