



tesa[®] Adhesive Strips for Transparent & Glass 1kg



Product Information

BNR 77733

Product Description

Refill pack for the Adhesive Hook for Transparent & Glass 1kg. For convenient reuse of the Adhesive Hook or to use alone.

Product Features

- Strip for reuse of the Adhesive Hook 1kg
- For transparent and solid surfaces indoors
- For medium weight objects up to 1kg per strip
- Strip can also be used alone without hook
- Removable without a trace

Application Fields

How to apply – Step by step 1. Before application, make sure the surface is free from grease and dirt with a silicone-free cleaner or methylated spirit.

2. After removing the foil, apply the Adhesive Strip to your surface. Press down for 5 seconds to activate the bonds. Be careful not to touch the adhesive area at any time.

3. If reusing an Adhesive Hook, apply it now. If using alone, press your object firmly on to the Adhesive Strip applying pressure for another 5 seconds.

4.. If used alone, leave the tab free behind your object, so you can grab and pull it for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------------------|------------------|-----------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power up to | 1 Kg |
| • Total thickness | 650 µm | • Silicone free | yes |
| • Holding power of strip up to | 1 Kg | | |



tesa[®] Adhesive Strips for Transparent & Glass 1kg

Product Information

Properties/Performance Values

• Application temperature from	-15 °C	• Residue-free removability	yes
• Area of use	Indoor	• Reusable	no
• Batteries included	no	• Reusable with	_NULL
• Batteries required	no	• Solvent free	yes
• Chemical Resistance	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Hazard material	no		
• Humidity resistance	no	• Temperature resistance max.	35 °C
• Material	_NULL	• Temperature resistance min.	5 °C
• Oil and grease resistance	no	• UV resistant	yes
• Ozone resistance	yes	• Waterproof	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>