



tesa® Insect Stop Pleated Alu Insect Screen For Roof Windows, Telescopic

Product Information

BNR 55804

Product Description

This insect screen pleated blind was specially developed for skylights. The telescopic aluminum profiles make installation easier, as there is no need to saw it. Thanks to the high-performance tesa Powerstrips®, the insect screen can be attached without drilling. This reduces installation time and the use of tools.

Product Features

- Innovative insect screen, pleated blind for skylights: Precise, adjustable telescopic profiles made of aluminum
- The insect screen especially made for skylights: Keeps flies and spiders out of the interior
- Mounting without drilling, screws and plugs: Effortless mounting with tesa Powerstrips® (provided the surface is stable)
- Time-saving installation - limited use of tools: Faster and less complicated than general solutions for protection against insects
- Gradual length adjustment: Thanks to telescopic side profiles, adjustable between 116 and 164 cm - without any sawing
- Pleated fabric can be shortened with the enclosed cutter: Width can be adjusted between 68 cm and 102 cm
- Telescopic sliding cassette: Adjustable to the desired width
- Suitable for windows positioned on an angled roof
- Stylish look: Side profiles and pleated cassettes are designed in white
- tesa's Fly Screen comes with a 5-year guarantee
- Can only be mounted on a flat roof surface

Properties/Performance Values

• Applicationfield	Home, Window	• Residue-free removability	yes
• Average installation time	0.45 hour(s)	• Reusable	yes
• Installation of products	Via adhesive tape / strips / liquid application	• Reusable with	Adhesive Strip 1kg Wallpaper
• Material	Aluminium	• Suitable surfaces	Wallpaper, Even wood
• Mesh	7.5 threads/cm	• Warranty	5 years



tesa[®] Insect Stop Pleated Alu Insect Screen For Roof Windows, Telescopic

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>