

tesa® Masking Tape Professional

Product Information

BNR 56270, 56271, 56212, 56299, 56245

Product Description

tesa® Masking Tape Professional, our best masking tape to date, guarantees razor-sharp and flat paint edges with its high-quality Washi tape paper, versatile adhesion, and residue-free removal for up to 6 months indoors and up to 2 months outdoors, ensuring professional high-quality results.

Sustainable Aspects

tesa® Masking Tape Professional is made with paper from well-managed, certified forests and other controlled sources

Product Features

- · For high quality masking paint tasks achieve expert quality results
- · Original Washi Paper for excellent and accurate sharp paint edges
- Residue-free removal for up to 6 months indoors and 2 months outdoors
- Flexible: Adapts well to a variety of surfaces made for indoor and outdoor painting projects
- · Suitable for all paints, lacquers, and glazes
- Easy to use: tesa® Masking Tape Professional is extra-tear-resistant
- · Made with paper sourced from responsibly managed forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	flat paper	•	Total thickness	90 μm
•	Type of adhesive	acrylic			

Properties/Performance Values

•	Tensile strength	30 N/cm	•	Batteries required	no
•	Applicationfield	Home	•	Hand tearability	yes
•	Area of use	In- and Outdoor	•	Tear resistance	yes

Batteries included no



tesa® Masking Tape Professional

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

