



tesa[®] Masking Tape Classic

Product Information

BNR 52805, 05282, 52807, 52803

Product Description

tesa[®] Masking Tape Classic is a all-round masking tape designed to enable clean paint jobs for indoor renovation work.

Product Features

- Enables exact, sharp edges on smooth and slightly rough surfaces without any paint dispersion
- Residue-free removal for up to 7 days indoors
- Suitable for all paints

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|---------|-----------------------------------|--------|
| • Tensile strength | 36 N/cm | • Residue-free removable after... | 7 days |
| • Applicationfield | Home | • Reusable | no |
| • Area of use | Indoor | • Solvent free | yes |
| • Batteries included | no | • Spare part service | no |
| • Batteries required | no | • Tear resistance | yes |
| • Hand tearability | yes | • Tensibility | 10 % |
| • Hazard material | no | • Writable | yes |
| • Residue-free removability | yes | | |



tesa[®] Masking Tape Classic

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>