



tesa® Powerstrips Poster

Product Information

BNR 58003, 58213, 64357

Product Description

Self-adhesive tesa Powerstrips Poster are the ideal means to attach posters to the wall without causing any damage to the wall and the poster itself.

Product Features

- Posters can be replaced or rearranged, leaving both surface and poster undamaged
- Secure hold of up to 200g*
- Removable without trace thanks to the Powerstrips® technology
- Usable even on sensitive surfaces like wallpaper or varnished surfaces
- Due to special shape, ideal for light and sensitive materials etc.

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

- Step by step - How to apply:
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Poster strip on the object - press for 5 seconds minimum
 3. Fix object onto surface - press for 5 seconds minimum
 4. Make sure the tab can be accessed for removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------------------|------------------|-----------------------|--------|
| • Type of adhesive | synthetic rubber | • Holding power up to | 0.2 Kg |
| • Total thickness | 400 µm | • Hook shape | _NULL |
| • Holding power of strip up to | 0.2 Kg | • Silicone free | yes |



tesa® Powerstrips Poster

Product Information

Properties/Performance Values

• Ageing resistance (UV)	yes	• Ozone resistance	yes
• Application temperature from	-15 °C	• Residue-free removability	yes
• Applicationfield	Kitchen, Living room, Children's room, Office, Hall, Bathroom	• Reusable	no
• Area of use	Indoor	• Reusable with	_NULL
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Chemical Resistance	no	• Temperature resistance max.	35 °C
• Hazard material	no	• Temperature resistance min.	5 °C
• Humidity resistance	no	• UV resistant	no
• Material	_NULL	• Waterproof	no
• Oil and grease resistance	no		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>