

tesa® Masking Tape Perfect+

Product Information

BNR 56536, 56538, 56537, 56539

Product Description

tesa® Masking Tape Perfect+ is a high-quality tape for different indoor painting jobs. The original Washi paper backing guarantees great accuracy for precise and flat paint edges every time. It is versatile and sticks to many surfaces such as plastered walls and wallpapers and is easy to remove. No traces are left behind, with excellent residue-free removal for up to 2 months indoors. Made with paper sourced from responsibly managed forests and other controlled sources, tesa® Masking Tape Perfect+ ensures optimal results.

Sustainable Aspects

tesa® Masking Tape Perfect+ is made with paper sourced from responsibly managed forests and other controlled sources

Product Features

- · Ideal for high quality indoor painting tasks achieve high-end results without paint splashes
- · Original Washi Paper: High quality for sharp, clean and defined paint edges
- Residue-free removal for up to 2 months indoors
- Flexible: Adapts well to a variety of surfaces to finely plastered walls, wallpapers, glass, aluminium, hard-PVC and wood
- Suitable for all paints, lacquers and glazes
- Easy to use: tesa® Masking Tape Perfect+ is convenient as it is tear-resistant

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	flat paper	•	Total thickness	85 μm
•	Type of adhesive	acrylic			

Properties/Performance Values

•	Tensile strength	32 N/cm	•	Batteries required	no
•	Applicationfield	Home	•	Hand tearability	yes
•	Area of use	Indoor	•	Residue-free removable after	60 days
•	Batteries included	no		days	
			•	Tear resistance	ves



tesa® Masking Tape Perfect+

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

