

# tesa<sup>®</sup> Adhesive Screw Rectangular for Brick & Stone 10kg



**Product Information** 

BNR 77908

## **Product Description**

Adhesive screw for up to 10kg. Ideal for mounting objects with narrow backs on rough and solid surfaces like brick and stone.

#### **Product Features**

- For rough and solid surfaces like brick & stone
- Holds up to 10kg per screw or 20kg using 2 screws
- Extra slim to hide behind narrow objects
- Removable from firm surfaces
- Suitable for indoor and outdoor use

## **Application Fields**

How to apply – Step by step1. Use a brush to get rid of as much grit or dust as you can from the surface to secure an optimal bond.

2. Peel off the protective foil from the adhesive foam tape and lightly press the adhesive screw to the surface. The foam tape is only used to keep the screw in place while you apply the adhesive. Make sure the screw head is aligned so that the body of the Adhesive Screw is hidden behind your object.

3. Pierce the nozzle on the tube of adhesive and pop the key over the other end.

4. Squeeze the adhesive into the bigger hole in the screw body by giving the key a twist. Continue until the adhesive begins to come out of the smaller hole and the cavity is filled evenly. Allow 12 hours for the adhesive to dry before you put weight on it.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

• Type of adhesive

Silane modified polymer

Holding power of strip up to 10 Kg



# tesa® Adhesive Screw Rectangular for Brick & Stone 10kg

yes

steel

no

Copper, Stainless

**Product Information** 

# **Properties/Performance Values**

•	Application	temperature from	5 °C
---	-------------	------------------	------

- Chemical Resistance yes
- Hazard material no
- Humidity resistance
- Material
- Oil and grease resistance

•	Ozone resistance	yes
٠	Residue-free removability	yes
٠	Reusable	no
•	UV resistant	yes
•	Waterproof	yes

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

