



tesa® 64500 PV10



Product Information

tesa® 64500US Standard Strapping Tape

Product Description

tesa® 64500 is a conventional strapping tape with a tensilized polypropylene backing and rubber adhesive. This adhesive system provides a secure bond while removing cleanly from various surfaces without adhesive residue or delamination. The mono-oriented polypropylene backing exhibits high conformability, good tensile strength, and low elongation. This allows for high performance in transport securing and surface protection of components in various industries, including office automation and home appliances. With effortless dispensing, our tape accommodates both manual and automatic operations.

Product Features

- solvent-free adhesive
- low elongation
- good workability

Application Fields

- Holding of appliance parts
- Securing printer and copier parts
- Holding and securing of peripherals
- High-performance surface protection
- Residue-free removability from a variety of different surfaces without discoloration
- High conformability to different shapes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | MOPP | • Total thickness | 105 µm |
| • Type of adhesive | synthetic rubber | • Color | orange |

Properties/Performance Values

- | | | | |
|-----------------------|----------|----------------|-----|
| • Elongation at break | 35 % | • Solvent free | yes |
| • Tensile strength | 255 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 7.5 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=64500>



tesa[®] 64500 PV10

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64500>