

tesa® extra Power Universal (>60% recycled backing)

Product Information

BNR 56348, 56388, 56389, 56490, 56396

Product Description

tesa® extra Power Universal is a versatile duct tape with extra bonding power, made with recycled materials. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Product Features

- · For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Backing made from more than 60% post-consumer recycled materials increasing sustainability and reducting waste!
- Very good adhesion to all types of surfaces
- · Weather-resistant for in-and outdoor applications
- · Tearable by hand
- · Solvent-free

Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE laminated cloth	•	Type of adhesive	synthetic rubber
•	Post-consumer recycled	67 %	•	Total thickness	215 μm
	content of backing				

Properties/Performance Values

 Elongation at break Tensile strength Abrasion resistance Adhesive strength Ageing resistance (UV) Application temperature from Application temperature to 	16 % 41.2 N/cm very good High adhesion yes 5 °C 60 °C	 Hand tearability Humidity resistance Residue-free removability Solvent free Suitable surfaces 	good yes no yes Even wood, Tiles, Most plastics, Glass, Metal
 Area of use 	In- and Outdoor	 Tear resistance 	yes
Chemical Resistance	yes	UV resistantWritable	yes yes



tesa® extra Power Universal (>60% recycled backing)

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

