



tesa[®] 88680

Product Information

15µm double sided transfer tape

Product Description

tesa[®] 88680 is a transparent, double-sided transfer tape consisting of a tackified acrylic adhesive.

Product Features

Thickness: 15µm

Excellent conformability and adjustment to uneven surfaces

Good converting and die-cutting performance

High adhesion level relative to low thickness

Excellent resistance to demanding environmental conditions

Application Fields

Components bonding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-----------------------------------|------------------|
| • Backing | none | • Color | translucent |
| • Type of adhesive | tackified acrylic | • Type of adhesive (covered side) | modified acrylic |
| • Type of liner | PE-coated paper | | |

Properties/Performance Values

- | | |
|-----------------------------------|------|
| • Static shear resistance at 23°C | good |
|-----------------------------------|------|

Adhesion to Values

- | | | | |
|-------------------|----------|------------------------|----------|
| • Steel (initial) | 3.3 N/cm | • Steel (after 3 days) | 4.4 N/cm |
|-------------------|----------|------------------------|----------|



tesa[®] 88680

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88680>