

# tesa® Ultra Power Under Water transparent

**Product Information** 

BNR 56481, 56491

# **Product Description**

The tesa® Ultra Power Under Water Transparent adhesive tape offers a reliable hold and protection in various conditions, such as moisture and heat. This makes it ideal for outdoor repairs, on wet surfaces, or underwater.

### **Product Features**

- Waterproof grip strength: This adhesive tape provides a reliable grip on wet surfaces and underwater
- Robust and durable: The extra-thick repair tape provides exceptionally strong adhesive strength
- Climate-proof resilience: UV and temperature resistance ensure effective repairs, at all times
- Resistance and flexibility: The abrasion-resistant repair tape adapts to various shapes and objects
- Versatile: Ideal for sealing holes, cracks, or leaks, both indoors and outdoors
- Discreet: The transparent adhesive tape blends seamlessly with any surface

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>	PVC film rubber based	Total thickness	730 µm
Properties/Performance Values			
<ul><li>Tensile strength</li><li>Abrasion resistance</li><li>Adhesive strength</li></ul>	90 N/cm yes Very high adhesion	<ul><li>Residue-free removability</li><li>Solvent free</li><li>Suitable surfaces</li></ul>	no no Most plastics, Steel,
<ul><li>Ageing resistance (UV)</li><li>Area of use</li></ul>	yes In- and Outdoor	Tear resistance	Glass, Metal yes
<ul> <li>Hand tearability</li> </ul>	no	Temperature resistance	yes
<ul> <li>Oil and grease resistance</li> </ul>	yes	UV resistant	very good
Ozone resistance	yes	<ul><li>Waterproof</li><li>Writable</li></ul>	yes no

Page 1 of 2 – as of 08/11/24 – en-US



# tesa® Ultra Power Under Water transparent

**Product Information** 

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 08/11/24 – en-US