



# tesa® 60404 Colored



## Product Information

Colored packaging adhesive film to securely seal boxes

## Product Description

tesa® 60404 is a premium packaging tape based on a PVC-film backing and a natural rubber adhesive. It shows excellent performance on all kind of cardboards and secures a safe closure. The natural rubber adhesive system is designed to show best results for applications on different kind of surfaces.

## Product Features

- Good adhesion even in recycled cartons
- Excellent tack and long-lasting adhesion
- Silent unwinding
- Ideal for storage in extreme temperature conditions and high moisture

## Application Fields

- Sealing small boxes (card-board or plastic)
- Sealing tins and bags
- Ideal for marking
- tesa® 60404 red enables a sharp-edge masking for multicolour painting

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                |                   |       |
|--------------------|----------------|-------------------|-------|
| • Backing          | PVC film       | • Total thickness | 67 µm |
| • Type of adhesive | natural rubber |                   |       |

## Properties/Performance Values

- |                       |      |                    |         |
|-----------------------|------|--------------------|---------|
| • Elongation at break | 90 % | • Tensile strength | 43 N/cm |
|-----------------------|------|--------------------|---------|

## Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 3.6 N/cm |
|---------|----------|

## Additional Information

tesa® 60404 is easily printable.

Available colors: red, blue, green, yellow and black

For latest information on this product please visit <http://l.tesa.com/?ip=60404>



# tesa<sup>®</sup> 60404 Colored

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60404>