



# tesa® Professional 60950

## Product Information



### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

• Material de soporte	PVC film coated with mineral particles	• Espesor de la cinta	720 µm
• Tipo de adhesivo	acrílico	• Espesor del protector	180 µm
• Espesor total	900 µm		

### Propiedades / Valores de rendimiento

• Elongación a la ruptura	25 %	• Fluorescente	no
• Resistencia a la rotura	30 N/cm	• Hand tearability	good
• Adecuado para troquelar	si	• Resistencia a los químicos	good
• Baterías incluidas	no	• Se requieren baterías	no
• Fácil de quitar	no		

### Adhesión a los valores

• Adhesión sobre acero	5.8 N/cm
------------------------	----------

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60950>