



tesa[®] 4316 PV3



Product Information

Cinta de enmascarar de papel para Pintado con Spray

Descripción del producto

tesa[®] 4316 es una cinta de enmascarar de papel crepado fino. El producto es delgado y flexible, por lo tanto es apropiado para aplicaciones generales de enmascarar, particularmente para pintura en spray, al igual que para aplicaciones de secado de pintura en horno hasta 100°C.

Características

- Thin and conformable backing
- Resistant to wet sanding
- Suitable for different paints and fillers
- Excellent adhesion for holding masks against overspray

Aplicación

Suitable for masking jobs with subsequent oven drying for temperatures up to 100°C.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado | • De base biológica (por peso) | 54 % |
| • Tipo de adhesivo | caucho natural | • Espesor total | 140 µm |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|---------|-----------------------------------------|-----------|
| • Elongación a la ruptura | 10 % | • Hand tearability | very good |
| • Resistencia a la rotura | 38 N/cm | • Resistencia a la temperatura (30 min) | 100 °C |
| • Fácil de quitar | si | | |

Adhesión a los valores

- | | |
|------------------------|----------|
| • Adhesión sobre acero | 3.4 N/cm |
|------------------------|----------|



tesa[®] 4316 PV3

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04316>