



tesa[®] 54678

Product Information

Hole Covering PET tejido , mayor conformabilidad

Descripción del producto

Tesa[®] 54678 Los cortes de troquel consisten en tela extruida de polietileno basada en una tela de PET / rayón tejida de 45 mesh que está recubierta con un adhesivo de caucho natural. Los troqueles se suministran en un revestimiento de vidrio amarillo.

Características

- Very good conformability to complex geometries
- Secure adhesion on almost any substrates
- High abrasion, puncture, and ageing-resistance
- Repositionable

Aplicación

tesa[®] 54678 is especially suitable at the assembly line for interior and exterior hole covering on all car body areas, e.g. pillars, rocker, front/rear floor.

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------------------|-----------------|--------|
| • Material de soporte | tejido extruido con PE | • Espesor total | 250 µm |
| • Tipo de adhesivo | caucho natural | | |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|-----------|---|--------------------------|
| • Elongación a la ruptura | 8 % | • Línea nítidas de corte | good |
| • Resistencia a la rotura | 50 N/cm | • Malla | 45 count per square inch |
| • Adecuado para troquelar | si | • Resistencia a la abrasión | good |
| • Hand tearability | very good | • Resistencia a la temperatura (30 min) | 95 °C |

Adhesión a los valores

- | | |
|------------------------|-----------|
| • Adhesión sobre acero | 4.25 N/cm |
|------------------------|-----------|

For latest information on this product please visit <http://l.tesa.com/?ip=54678>



tesa[®] 54678

Product Information

Additional Information

We would like to recommend our stock assortment, which includes the following dimensions:
circles: 19 / 30 / 40 / 50 mm diameter

tesa[®] 54678 is available upon request in customer specific dimensions and can be delivered in either roll form or as sheets.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54678>