



tesa® 4322

Product Information



Cinta de enmascar de papel para Pintado con Spray

Descripción del producto

Tesa® 4322 es una cinta de enmascarar de papel de uso general altamente crêped para diversos campos de aplicación y es especialmente adecuada para el enmascaramiento de curvas.

Sustainable Aspects

65% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Características

tesa® 4322 is a highly crêped, general purpose paper masking tape for various application fields and is especially suitable for masking of curves.

Aplicación

The product is particularly recommended for all standard masking work in painting and paint spraying with air drying paints. The extremely high stretch capacity of the flexible backing guarantees - even in narrow curves - a good adhesion. Good flexibility allows adhesion to complicated contours and rough surface. It is also suitable for fixing of paper masks, for packaging and bundling purposes and for masking before under sealing. tesa® 4322 is also used for strenghtening uppers in the shoe industry.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------|--|--------|
| • Material de soporte | papel crepado | • Total sustainable product excl. liners by weight (acc. EN 16785) | 65 % |
| • Tipo de adhesivo | caucho natural | • Espesor total | 380 µm |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 58 % | • Fácil de quitar | si |
| • Resistencia a la rotura | 58 N/cm | • Hand tearability | very good |

For latest information on this product please visit <http://l.tesa.com/?ip=04322>



tesa[®] 4322

Product Information

Adhesión a los valores

- Adhesión sobre acero 5 N/cm

Additional Information

Recommendation:

Stretching the crêped backing guarantees evenly defined paint edges and a good adhesion.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04322>