



# tesa<sup>®</sup> 4318 PV2



## Product Information

Cinta de enmascarado de alta performance - 160°

## Descripción del producto

Tesa<sup>®</sup> 4318 PV2 es una cinta adhesiva de papel finamente crêpida y flexible, especialmente adecuada para requerimientos de pintura seguida de secado en horno.

## Características

- The natural rubber adhesive offers high tack and excellent adhesion on a variety of surfaces like metal, rubber, glass and plastic.
- The excellent adherence of fillers or paints (water- or solvent-based) to the reverse side of the tape prevents any kind of paint flaking, even after the oven-drying process with temperatures of up to 160 °C.
- It can be easily removed without leaving any residues.
- The conformable masking tape is resistant to wet sanding and can withstand high temperatures, making it suitable for oven-drying.

## Aplicación

- Suitable for temperatures up to 160°C - ideal for demanding automotive masking jobs during spray painting
- High adhesion on various surfaces (metal, rubber, glass, plastic) and holds masks securely
- Excellent paint anchorage on reverse side

## Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

## Composición del producto

- |                       |                |                                |        |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado  | • De base biológica (por peso) | 52 %   |
| • Tipo de adhesivo    | caucho natural | • Espesor total                | 170 µm |

## Propiedades / Valores de rendimiento

- |                           |         |                    |           |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 12 %    | • Fácil de quitar  | si        |
| • Resistencia a la rotura | 47 N/cm | • Hand tearability | very good |

## Adhesión a los valores

- |                        |        |
|------------------------|--------|
| • Adhesión sobre acero | 4 N/cm |
|------------------------|--------|



# tesa<sup>®</sup> 4318 PV2

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04318>