



tesa[®] 4308

Product Information



Premium Masking Tape for High Demanding Paint Applications

Descripción del producto

tesa[®] 4308 is a smooth crepe paper masking tape with a natural rubber adhesive, which has been developed especially for highly demanding masking applications in the automotive aftermarket and transportation industries. The adhesive tape is suitable for masking during spray painting with following oven drying, resisting temperatures up to 110°C.

tesa[®] 4308 can be used either with 2-component or waterborne paints. The backing resists bleed through of paint, and is highly conformable and flexible. The masking tape features excellent adhesive properties on different substrates like metal, rubber, glass and plastic, as well as high tack and good quick stick.

Sustainable Aspects

50% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Características

- The smooth crepe paper backing provides excellent conformability and is also finger friendly.
- Vivid blue color allows high visibility.
- Strong adhesion to various surfaces like metal, rubber, glass and plastic.

Aplicación

- Ideally for demanding masking applications in automotive industry, car body repair and transportation industry.
- Suitable for oven drying resisting temperatures of up to 110°C

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------|--|--------|
| • Material de soporte | papel crepado | • Total sustainable product excl. liners by weight (acc. EN 16785) | 50 % |
| • Tipo de adhesivo | caucho natural | • Espesor total | 170 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04308>



tesa[®] 4308

Product Information

Propiedades / Valores de rendimiento

• Elongación a la ruptura	13 %	• Conformable	good
• Resistencia a la rotura	53 N/cm	• Fácil de quitar	si
• Buen anclaje de la pintura	very good	• Hand tearability	very good
• Color en el borde definido	very good		

Adhesión a los valores

- Adhesión sobre acero 4 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04308>