



tesa[®] 4101 PV2



Product Information

Office film with a hydrate cellulose backing

Descripción del producto

tesa[®] 4101 PV 2 consists of a hydrate cellulose film coated with a rubber adhesive.

Características

- The backing is characterized by a high rigidity and low electrostatic charging
- Long strips of the tape can be dispensed without any curling effect is possible
- Hydrate cellulose film can be cleanly cut (separated) by an subjacent tesa[®] tear strip.
- The tape can easily be torn by hand

Aplicación

tesa[®] 4101 PV 2 is mainly used for general purpose stationary and office applications, such as sealing of small boxes, envelopes or light weight cartons. The tape can easily be applied with tesa[®] desk dispensers.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------------------|-----------------|-------|
| • Material de soporte | hidrato de celulosa | • Espesor total | 51 µm |
| • Tipo de adhesivo | caucho natural y sintético | | |

Propiedades / Valores de rendimiento

- | | | | |
|------------------------------|---------|--------------------|----|
| • Elongación a la ruptura | 25 % | • Hand tearability | si |
| • Resistencia a la rotura | 42 N/cm | • Transparencia | si |
| • Baja fuerza de desbobinado | si | | |

Adhesión a los valores

- | | |
|------------------------|--------|
| • Adhesión sobre acero | 5 N/cm |
|------------------------|--------|



tesa[®] 4101 PV2

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04101>