



tesa® 64624

Product Information



Double-sided filmic tape

Descripción del producto

tesa® 64624 is a transparent double-sided filmic tape based on a PP backing and a well-balanced synthetic rubber adhesive.

tesa® 64624 has been designed to meet the requirements of trim and profile producers:

Características

- Good unwinding properties
- Low risk of product tearing due to filmic backing
- No adhesive oozing during the transport of the trims
- Paper liner to withstand fast liner removal without tearing
- Well balanced adhesive offers high immediate adhesion and very good shear strength at sufficient tack at room temperature
- Recycling friendly according to the INGEDE method

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------------|-------------------------|---------------------|
| • Material de soporte | film PP | • Color | transparente |
| • Tipo de adhesivo | caucho sintético | • Color del protector | marrón |
| • Tipo de protector | glassine | • Espesor del protector | 76 µm |
| • Espesor total | 175 µm | • Gramaje del protector | 90 g/m ² |

Propiedades / Valores de rendimiento

- | | | | |
|----------------------------|---------|-------------------------------------------------|-----|
| • Elongación a la ruptura | 140 % | • Resistencia al cortante (cizalladura) a 40 °C | low |
| • Resistencia a la rotura | 45 N/cm | • Resistencia al envejecimiento (UV) | low |
| • Resistencia a la humedad | medium | • Tack | low |

Adhesión a los valores

- | | | | |
|-------------------------------|---------|----------------------------------|---------|
| • Adhesión sobre PC (inicial) | 13 N/cm | • Adhesión sobre PVC (inicial) | 13 N/cm |
| • Adhesión sobre PE (inicial) | 10 N/cm | • Adhesión sobre Acero (inicial) | 12 N/cm |
| • Adhesión sobre PP (inicial) | 8 N/cm | | |

For latest information on this product please visit <http://l.tesa.com/?ip=64624>



tesa[®] 64624

Product Information

Additional Information

Liner variants:

PV 00 Brown glassine liner

PV 01 White glassine liner (84µm/102gr)

PV 06 Red MOPP filmic liner (80µm/71gr)

For spools, it is recommended to use tesa[®] dispensers to achieve optimal results.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64624>