



tesa® 4341

Product Information



Cinta de enmascarar para pintado por spray resistente a 140°

Descripción del producto

Tesa® 4341 es una cinta adhesiva de papel finamente crêpida, extremadamente extensible y flexible para pintar. Su adhesivo de caucho natural, libre de disolventes, ofrece propiedades bien equilibradas en términos de adhesividad, resistencia a la cizalla ya la temperatura.

Sustainable Aspects

55% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Características

- The conformable masking tape is resistant to wet sanding and can withstand high temperatures, making it suitable for oven-drying.
- The excellent adherence of fillers or paints (water- or solvent-based) to the reverse side of the tape prevents any kind of paint flaking.
- Even after the oven-drying process with temperatures of up to 140 °C, tesa® 4341 can be easily removed without leaving any residues.

Aplicación

- tesa® 4341 is a temperature-resistant masking tape, ideal for demanding masking tasks during spray painting
- The high-temperature tape can be used with various surfaces like metal, rubber, glass, and plastic
- The conformable tape is suitable for fixing of heavy and big masks
- tesa® 4341 offers excellent paint anchorage on reverse side
- Ambitious lacquering work
- Suitable for sensitive surfaces
- Good flexibility for curves
- Fixing heavy masking material

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado | • De base biológica (por peso) | 55 % |
| • Tipo de adhesivo | caucho natural | • Espesor total | 190 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04341>



tesa[®] 4341

Product Information

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 13 % | • Fácil de quitar | si |
| • Resistencia a la rotura | 53 N/cm | • Hand tearability | very good |

Adhesión a los valores

- | | |
|------------------------|----------|
| • Adhesión sobre acero | 4.7 N/cm |
|------------------------|----------|

Additional Information

La cinta es resistente al lijado en húmedo y la excelente adhesión de rellenos o pinturas (base de agua o solventes) al lado reverso de la cinta evita cualquier tipo de despegado.

Incluso después del proceso de secado en horno con temperaturas hasta 140°C, tesa[®] 4341 puede ser fácilmente retirado sin dejar residuos.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04341>