



tesa® 6068

Product Information



Dispenser de banco automático

Descripción del producto

tesa® 6068 es un dispensador totalmente automático con longitud predeterminada de corte y cantidad de piezas ajustable, y corte por foto sensor. Se puede usar con prácticamente todo tipo de cintas tesa® con un ancho de hasta 50mm, especialmente con cintas de fleje, de filamentos y cintas de tejido. Este dispensador tiene un display digital, y memoria, la máquina memoriza el último trabajo, medidas y número de tiras. Permite el uso de cintas de una cara y de cintas doble cara con el protector de hasta 1,5mm de espesor total. En el caso de dispensar cintas de doble cara, el protector debe ser retirado a posteriori.

Características

- This dispenser has a digital display, a storage of the preset length and a counter for the number of cut pieces.
- This dispenser can be used for s/s as well as d/s-tapes including liner up to approximately 1,5mm thickness.

Aplicación

Release the roller lock lever and put the tesa® tape into the adjustable tape holder. Feed the tape by using the FORWARD button and fix it afterwards with the hold down roller unit and the tape holder. The desired tape length is set by the SET A- and SET B- button in a range from 5 to 999 mm. The desired number of pieces is set by the SELECT button. Press the START button to deliver the tape.

Propiedades / Valores de rendimiento

- | | | | |
|-----------------------------|----------|----------------------|----------------|
| • Core diameter | 3 | • Gramaje | 2500 g |
| • Diámetro máximo del rollo | 300 mm | • Modo de operación | automático |
| • Fijado le longitud | 5-999 mm | • Tipo de aplicación | multifuncional |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06068>