

# 51918

## FilmLine Black

### Product Information

Integrated splicing tape



### Descripción del producto

#### Components

- polyester backing
- paper based splitting mechanism
- modified synthetic rubber adhesive

### Características

- Slit liner for the secure fixation of the top layer
- Robust polyester backing for secure splicing even at high web tension
- Double-sided black backing for optical detection of the splice at the reel stand or in following processes
- High tack properties and good adhesion on unpolar surfaces for excellent contact between expiring web and new reel
- One splitting strip with tailored opening characteristics for a smooth opening of the new reel without jeopardizing the converting process

### Aplicación

The tape is particularly suitable for high speed flying splice applications in any kind of film converting processes like flexo and rotogravure printing as well as laminating processes.

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |                  |                 |        |
|-----------------------|------------------|-----------------|--------|
| • Material de soporte | PETP             | • Espesor total | 105 µm |
| • Tipo de adhesivo    | caucho sintético | • Color         | negro  |

### Propiedades / Valores de rendimiento

- |                           |         |                      |           |
|---------------------------|---------|----------------------|-----------|
| • Elongación a la ruptura | 60 %    | • Caducidad (envase) | 18 months |
| • Resistencia a la rotura | 70 N/cm |                      |           |



# 51918

## FilmLine Black

Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51918>