



# tesa® 54715 Noise Blocker Standard



## Product Information

Pieza troquelada para Hole Covering con propiedad isonorizante

## Descripción del producto

Tesa® 54715 es una poliolefina de gran densidad mineral con alta capacidad adhesiva para cubrir los orificios no utilizados en la carrocería que requieren aislamiento acústico y un montaje seguro incluso en áreas de aplicación difíciles de alcanzar.

Características:

- Alta densidad de área de 1.8kg / m<sup>2</sup> \* Reduce significativamente y absorbe el ruido independientemente del tamaño del agujero para mejorar el confort acústico durante la conducción
- Rápido y fácil de instalar y el adhesivo especialmente elegido hace que sea fácil de lograr

un buen sello

## Características

- Excellent acoustic insulation due to high area density 1.8kg/m<sup>2</sup>
- Secure adhesion on almost all substrates
- Good sealing properties

## Aplicación

tesa® 54715 is especially suitable at the assembly line for interior hole covering on all car body areas, e.g. pillars, rocker, front/rear floor.

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

## Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

## Composición del producto

- |                       |                     |                 |         |
|-----------------------|---------------------|-----------------|---------|
| • Material de soporte | poleofina           | • Espesor total | 1140 µm |
| • Tipo de adhesivo    | acrílico modificado | • Color         | gris    |
| • Tipo de protector   | glassine            |                 |         |

## Propiedades / Valores de rendimiento

- |   |        |                          |                 |
|---|--------|--------------------------|-----------------|
| • Resistencia a la temperatura (30 min) | 100 °C | • Resistencia al punzado | 215 N           |
| • Resistencia a los químicos            | good   | • Resistente a llama     | autoextinguible |

For latest information on this product please visit <http://l.tesa.com/?ip=54715>



# tesa<sup>®</sup> 54715 Noise Blocker Standard

## Product Information

### Additional Information

tesa<sup>®</sup> 54715 can be supplied as die-cuts in roll or sheets individually to customer specific dimensions. Our application process engineers support with customized equipment and self-designed application tools to enhance productivity.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54715>