



# tesa® 7133

## Product Information



Film de protección y enmascarado de superficies

### Descripción del producto

tesa® 7133 es un film autoadhesivo de polipropileno con un adhesivo de caucho natural.

### Características

- Thin backing with a temperature resistance up to 120°C/1h
- Non-conformable PP backing for straight line applications
- Natural adhesive that works on glass and high surface energy plastic parts
- The thin 80 µm backing allows the creation of thin paint split lines.
- With a temperature resistance of up to 120°C, tesa® 7133 can be used in masking applications with a low- to medium-temperature exposure.

### Aplicación

tesa® 7133 is suitable for various types of masking and temporary interior surface protection applications.

Example applications are:

- Straight line masking during multicolor painting at low to medium temperatures
- Temporary protection against dirt and damage of painted and unpainted plastic parts (ABS, PC, PMMA)

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |                |                 |       |
|-----------------------|----------------|-----------------|-------|
| • Material de soporte | film PP        | • Espesor total | 80 µm |
| • Tipo de adhesivo    | caucho natural |                 |       |

### Propiedades / Valores de rendimiento

- |                           |          |                       |           |
|---------------------------|----------|-----------------------|-----------|
| • Elongación a la ruptura | 30 %     | • Fácil de quitar     | si        |
| • Resistencia a la rotura | 133 N/cm | • Retardante de llama | very good |

### Adhesión a los valores

- |                        |          |
|------------------------|----------|
| • Adhesión sobre acero | 1.8 N/cm |
|------------------------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=07133>



# tesa<sup>®</sup> 7133

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07133>