



# tesa® 6037

## Product Information



Dispenser de banco semiautomático

### Descripción del producto

tesa® 6037 es un dispensador que permite ajustar la longitud deseada de cinta. Diseñado para el sellado de pequeños paquetes. Su tamaño compacto asegura una buena estabilidad sin necesidad de tener que ser atornillado a la mesa de trabajo. La longitud de cinta preseleccionada es dispensada presionando la palanca. La cinta se corta con una cuchilla de diente de sierra al reitarla. La longitud máxima de cinta que se puede ajustar es de 10 cm. El soporte del mandril admite rollos con mandril de 1" y de 3" de diámetro.

### Características

- The compact size of the dispenser ensures that it remains stable without having to be screwed down.

### Aplicación

To insert the tesa® roll, the tape wheel must be withdrawn and the blade holder removed. The tesa® tape is placed on the tape wheel and then both parts are replaced in the dispenser. The start of tape should be placed with the adhesive side downwards onto the upper transporting roller. When operating the transport lever, the tape is automatically threaded beneath the blue profile roll. Now reposit the blade holder to make the tesa® 6037 automatic dispenser ready for use. By loosening the knurled screw of the transport lever, the lever position and consequently the pre-set tape length can be altered.

### Propiedades / Valores de rendimiento

• Core diameter	3	• Modo de operación	manual
• Diámetro máximo del rollo	140 mm	• Roll width max	30 mm
• Fijado le longitud	100 mm	• Tipo de aplicación	multifuncional
• Gramaje	1400 g		

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06037>