



72426 FE



Product Information

Cinta de Espuma de 500 µm para Montaje de Fotopolimeros: FE - Medium Hard

Descripción del producto

Cinta de espuma de doble cara

Propiedades de espuma

- Baja tolerancia de grosor
- Larga duración, características de recuperación constante

Propiedades adhesivas

- Características de superficie de baja adherencia
- Mejor unión de placas
- Fácil desmontaje de placas
- Banda adhesiva suficiente hacia el lado de la manga

Propiedad adicional

- PP-forro estructurado para evitar la formación de bolsas de aire cuando la placa se monta

Características

- Foam properties: Low thickness tolerance. Long lasting, constant recovery characteristics.
- Adhesive properties: Low tack surface characteristics. Best plate bonding. Easy plate demounting. Sufficient tape bonding towards sleeve side.
- Additional property: Structured PP-liner to prevent formation of air pockets when the plate is mounted.

Aplicación

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|--------------------------------|---------------------|--------|
| • Material de soporte | Espuma PE con un film laminado | • Tipo de protector | PP |
| • Tipo de adhesivo | acrílico modificado | • Espesor total | 550 µm |

Propiedades / Valores de rendimiento

- | | | | |
|------------------------|------|----------|------------|
| • Categoría de espesor | 500 | • Dureza | medio duro |
| • Color del logotipo | azul | | |

For latest information on this product please visit <http://l.tesa.com/?ip=72426>



72426

FE

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=72426>