



tesa[®] 4139 empalme siliconado



Product Information

Cinta de empalme simple faz para materiales siliconados

Descripción del producto

Tesa[®] 4139 es una cinta transparente con soporte PETP. Su sistema adhesivo de silicona ofrece una excelente adherencia a superficies "antiadherentes" / siliconizadas.

Color: Transparente

Características

- Its silicone adhesive system offers excellent adhesion to "non-stick"/siliconized surfaces.

Aplicación

The silicone release coating on the backing of tesa[®] 4139 makes it ideally suited for the splicing of paper and filmic release liners.

Its coating maintains the release properties of the liner materials in the splice area.

The very low thickness of tesa[®] 4139 makes it suitable splicing applications, for very sensitive machinery.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- Espesor total 80 µm

Propiedades / Valores de rendimiento

- Elongación a la ruptura 40 %
- Resistencia a la rotura 30 N/cm

Adhesión a los valores

- Adhesión sobre silicona 3.5 N/cm
- Adhesión sobre acero 4.5 N/cm



tesa[®] 4139

empalme siliconado

Product Information

Additional Information

The product's shelf-life is 6 months.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04139>