



tesa[®] 4563 PV3



Product Information

Cinta siliconizada para recubrimiento de cilindros

Descripción del producto

tesa tesaband lisa (Printer's Friend[®]) 4563 es una cinta de tela laminada con caucho siliconado, con excelentes propiedades de agarre, además repele una gran variedad de sustancias. El diseño del producto garantiza una alta resistencia al desgaste, la vuelve de fácil aplicación. No deja residuos al removerla, incluso después de periodos de tiempo prolongados y exposición a altas temperaturas.

Aplicación

tesa Printer's Friend[®] 4563 is specially designed for roller wrapping applications. In many cases, a new covering may be applied without removing the roller from the machine.

Industries include:

- *Printing industry
- *Textiles industry
- *"Focus" label printing machinery
- *General, web-based processing & converting industries

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|-------------------------------|-------------------------|--------|
| • Material de soporte | tejido recubierto de silicona | • Espesor total | 380 µm |
| • Tipo de adhesivo | caucho natural | • Espesor del protector | 80 µm |
| • Tipo de protector | PP | | |

Adhesión a los valores

- Adhesión sobre acero 4.1 N/cm

Additional Information

- The product's shelf life is 12 months.
- 4563 PV2 - Here the only difference compared to the PV0 is the adhesion to steel of 3,2N/cm



tesa[®] 4563 PV3

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04563>