



tesa[®] 74280

Product Information



BOPP packaging tape with synthetic rubber adhesive

Product Description

tesa[®] 74280 is a 42µm packaging tape featuring a conformable BOPP backing and a synthetic rubber adhesive. The tacky adhesive provides an instant adhesion to most paper qualities, including test liner with high recycled content. It can be used for both manual and automated tape application. tesa[®] 74280 is a reliable choice for boxes up to 15 kg in the food & beverages, cosmetics, chemicals, textiles, furniture and other manufacturing industries.

Product Features

- Packaging tape for manual and automated application
- High tack synthetic rubber adhesive for most carton qualities
- Conformable, filmic BOPP backing (25µm)
- Easy unwinding

Application Fields

- Carton sealing
- Manual and automated application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 42 µm |
| • Type of adhesive | synthetic rubber | | |

Product Assortment

- | | |
|--------------------|--------------------|
| • Available colors | brown, transparent |
|--------------------|--------------------|

Properties/Performance Values

- | | | | |
|-------------------------|---------|-----------------------|-------------|
| • Elongation at break | 100 % | • Low unwinding force | yes |
| • Tensile strength | 30 N/cm | • Packaging Weight | Up to 15 kg |
| • Automatic application | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.6 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=74280>



tesa[®] 74280

Product Information

Additional Information

Tape application is best accomplished at ambient temperatures from 10°C to 40°C. Once applied it performs well throughout the normal temperature range in typical shipping and storage conditions.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=74280>