



tesa[®] 53799 PV2



Product Information

Polyethylene coated high grade cloth tape

Product Description

tesa[®] 53799 is a polyethylene coated high grade cloth tape. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive.

tesa[®] 53799 is a very strong cloth tape for a wide range of applications, especially used by the army.

Product Features

- very good adhesion, even on rough surfaces
- excellent tensile strength
- water repellent
- conformable
- available in olive green

Application Fields

Convenient for different repairing and construction applications, including the military area e.g.

- Packaging
- Bundling
- Closing, covering and fixing
- Repairing of hoods
- Splicing of awnings
- Multipurpose applications in the agriculture

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|---------------------|----------|
| • Backing | PE extruded cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | • Thickness of tape | _NULL µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------------------|-----------------------------------|--------|
| • Elongation at break | 11 % | • Straight tear edge | good |
| • Tensile strength | 77 N/cm | • Temperature resistance (30 min) | 110 °C |
| • Abrasion resistance | good | • Temperature resistance | 110 °C |
| • Hand tearability | good | (removability from aluminum | |
| • Mesh | 80 count per square | after 30 min exposure) | |
| | inch | • Water resistance | good |

For latest information on this product please visit <http://l.tesa.com/?ip=53799>



tesa[®] 53799 PV2

Product Information

Adhesion to Values

- Steel 4.7 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53799>