



tesa[®] 4333 Precision Mask[®] Sensitive



Product Information

High grade paper masking tape for precise and flat paint edges on sensitive surfaces

Product Description

tesa[®] 4333 Precision Mask Sensitive consists of an extra-thin and strong paper backing coated with a natural rubber adhesive.

The highly equipped and flat backing material makes the product highly conformable on various surfaces. Additionally the outstanding special adhesive formulation has got an application relevant adhesive power needed for masking applications on sensitive and critical surface. This allows an easy removability up to 1 week after application which enables multiple working processes in only one covering process.

Application Fields

This tape is suited for almost all indoor paint works

tesa[®] 4333 Precision Mask Sensitive is applicable with water-based paints and lacquers and fits even for high-class spatula techniques.

It is especially designed for applications on sensitive and critical surfaces.

The flat backing material is highly conformable to the surface and leads to precise razor-sharp paint edges.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|-------|
| • Backing | flat paper | • Total thickness | 85 µm |
| • Type of adhesive | acrylic | • Color | pink |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-----------|
| • Elongation at break | 4.5 % | • Hand tearability | very good |
| • Tensile strength | 41 N/cm | • Suitable for rough surfaces | medium |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 0.6 N/cm |
|---------|----------|



tesa[®] 4333 Precision Mask[®] Sensitive

Product Information

Additional Information

Please note that adhesive tapes should not be left on sensitive surfaces for longer than one week as residues during the de-masking might occur after that. Before using an adhesive tape on a delicate surface, please make a trial application for up to 24 hours.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04333>