

tesa® Softprint 73522 neXt FE-X (EA)

Product Information

Foam plate mounting tape: FLEX Product Design

Product Description

tesa® Softprint neXt 73522 FE-X (EA), a double-sided foam tape, with the new innovative adhesive package enables an effortless plate handling through unique features now for every step.

This makes tesa® Softprint neXt 73522 FE-X (EA) an unrivaled solution for unmatched efficiency and user satisfaction.

Product Features

Presenting tesa® Softprint neXt, our new plate mounting solution that offers neXt level performance throughout the whole process:

- · Low tack for easy plate repositioning during mounting
- Outstanding performance against edge lifting during printing
- Innovative plate side adhesive for improved and easy removal avoiding damage to the printing plate during demounting

Application Fields

Mounting of 1.14mm (0.045") and 1.70mm (0.067") flexographic printing plates onto steel/ alu/ PU and glassine cylinders.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE foam with film	•	Type of liner	PET
		lamination	•	Total thickness	550 μm

Type of adhesive tackified acrylic

Properties/Performance Values

•	Color of foam	red •	Thickness category	500
•	Hardness	soft		

Additional Information

- Foam properties: Low thickness tolerance. Long lasting, constant recovery characteristics.
- Additional property: Flexible PE reinforcement film to compensate for the expansion of thin walled sleeves.
- Liner: Transparent structured easy application (EA) PET liner for excellent air removal during plate and tape mounting.





tesa® Softprint 73522 neXt FE-X (EA)

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

