



tesa[®] Aluminium Tape

Product Information



BNR 56223

Product Description

tesa[®] Aluminium tape is a special self-adhesive plumbers tape perfectly suited to quickly repair any metal surface, such as heating appliances or gutters.

Caratteristiche

- Suitable for protecting, covering, insulating and repairing
- * May also be used for roof and gutter repairs
- * Temperature resistant from -40°C to +160°C
- * Water-, oil- and grease-resistant
- * Age-resistant
- * High adhesive strength

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------|----------------|-------------------|--------|
| • Supporto | aluminium foil | • Spessore totale | 100 µm |
| • Massa adesiva | acrylic | | |



tesa[®] Aluminium Tape

Product Information

Proprietà/Valori di prestazione

• Resistenza alla trazione	15 N/cm	• Resistenza all'umidità	yes
• Adesività	High adhesion	• Resistenza alla temperatura	yes
• Area d'uso	Indoor and Outdoor	• Resistenza massima alla temperatura	160 °C
• Batterie incluse	no	• Resistenza min. alle temperature	-40 °C
• Batterie richieste	no	• Rimozione senza residui	no
• Campo di applicazione	Garage, Auto, Tetto, A casa, Giardino, Soffitto	• Riutilizzabile	no
• Materiale	Alluminio	• Scrivibile	no
• Resistente agli oli e lubrificanti	yes	• Servizio pezzi di ricambio	no
• Resistente ai raggi UV	yes	• Superfici adatte	Vetro
• Resistente all'acqua	yes	• Tensione	5 %
• Resistenza all'abrasione	no		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>