



tesa® 50110

Product Information



Natural rubber coated cloth tape

Product Description

tesa® 50110 is a strong natural rubber coated cloth tape. It is based on a 148 mesh woven rayon fabric backing and a natural rubber adhesive. tesa® 50110 is an all-round cloth tape for a wide range of applications, often used for belting of components.

Features:

- High adhesion, even on rough surfaces
- Very high tensile strength
- Abrasion-resistant

Application Fields

- Marking of wires and cables
- Bundling of pipes, profiles etc.
- Noise and scrub protection
- Harnessing
- Securing of sharp edges
- Sealing of cartons, tins and tubes
- Belting of components, nails, screws, bicycle, rims etc.
- Floor marking * Sandblasting
- Floor coating

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 300 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|-----------------------------------|---------------------------|
| • Elongation at break | 12 % | • Hand tearability | very good |
| • Tensile strength | 100 N/cm | • Mesh | 145 count per square inch |
| • Abrasion resistance | very good | | |
| • Available as Spools | no | • Straight tear edge | very good |
| • Easy to remove | yes | • Temperature resistance (30 min) | 140 °C |
| • Easy to write on | yes | • Water resistance | good |

For latest information on this product please visit <http://l.tesa.com/?ip=50110>



tesa[®] 50110

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50110>